

FLEX ABS 140 COMBI Y

REF.NO. 7W920*O



Compact and lightweight fall arrest lanyards equipped with energy absorbers, high-elastic arms and BIG terminal connectors (Ref. No. 2C35300V1A).

Main features:

- innovative SLIDER (patented) energy absorber with progressive tear, protected by a strong zip-case;
- elastic arms made with a reinforced band that enables a significant reduction of the encumbrance while using them and they elongate following the operator's movement;
- work load limit: 140 kg;
- equipped with light alloy double gate connectors and with a maximum gate opening of 60 mm;
- compliant with the requirements of RFU PPE-R/11.074 for horizontal and inclined use over an edge ($r \geq 0,5$ mm);
- available with elastic arms in two different lengths.

STANDARD AND ADDITIONAL INFORMATION

EN 355:2002

RFU 11.074

CE 0333



MADE IN
EUROPE

FLEX ABS 140 COMBI Y

REF.NO. 7W920*O



TABLES

Model	Ref. No.	Length	"A" length	Weight
FLEX ABS 140 COMBI Y-S	7W920115O	115 cm	125 cm	1220 g
FLEX ABS 140 COMBI Y-L	7W920180O	180 cm	190 cm	1320 g

A: Length of the product including connectors; conventional connector length: 10 cm.

GALLERY

